

DETECTORS - DUAL TECHNOLOGY

Mouse

EN 50131-2-4

GRADE 3

(Mouse 02 - Mouse 02/P)



Pet Immunity



Anti Masking


10 YEARS
warranty



Simplified assembly without screws




RFI digital protection



White light digital filter protection



New Tamper



EOL resistors on board

BRACKET SN2
(wall bracket)



BRACKET SN4
(wall / ceiling bracket)





Mouse02

EN 50131-2-4 / **GRADE 3**
Dual Technology
ANTI-MASKING detector
with EOL resistors

Mouse02/P

EN 50131-2-4 / **GRADE 3**
Dual Technology
ANTI-MASKING detector
with EOL resistors
PET IMMUNE up to 15 kg



Mouse09

EN 50131-2-4 / **GRADE 2**
Dual Technology detector
with EOL resistors

Mouse09/P

EN 50131-2-4 / **GRADE 2**
Dual Technology detector
with EOL resistors
PET IMMUNE up to 15 kg



Mouse02 is antimask dual technology detector with analysis system that takes into account the two most important changes that may occur during a movement: the speed and the intensity. With the simultaneous comparison of these two information, the detector is able to discriminate repetitive movements from intrusion, lowering the percentage of false alarms. The totally digital temperature compensation system, guarantees a great performance. Is equipped with internal EOL resistors. Has 15 mt coverage, with angle of 90°. With the special lens is equipped of creep zone. **Available colours:** white

Mouse09 is a dual technology detector with an analysis system that takes into account the two most important changes that may occur during a movement: the speed and the intensity. With the simultaneous comparison of these two information, the detector is able to discriminate repetitive movements from intrusion, lowering the percentage of false alarms. With high thermal variations, the totally digital temperature compensation system, guarantees a great performance. Is equipped with internal EOL resistors. Has 15 mt coverage, with angle of 90°. With the special lens is equipped of creep zone. **Available colours:** white

TECHNICAL FEATURES

	MOUSE 02	MOUSE 09	MOUSE 02/P	MOUSE 09/P
EN 50131-2-4 / GRADE 2	-	YES	-	YES
EN 50131-2-4 / GRADE 3	YES	-	YES	-
RANGE	15 mt	15 mt	15 mt	15 mt
ANGLE	90°	90°	90°	90°
ALARM TIME	2"	2"	2"	2"
SELF TEST	YES	-	YES	-
WALK TEST'S LED	YES	YES	YES	YES
MICROWAVE FREQUENCY	9.3 - 9.9 - 10.5 Ghz			
SOLID STATE RELAY	YES	YES	YES	YES
INTERNAL EOL RESISTORS	1K, 2k2, 4k7, 5k6, 8k2			
CREEP ZONE	YES	YES	YES	YES
ANTIOPENING TAMPER	YES	YES	YES	YES
ANTIMASKING DEVICE	YES	-	YES	-
PULSE COUNTER	YES	YES	YES	YES
RFI PROTECTION	30 V/m	30 V/m	30 V/m	30 V/m
TEMPERATUR COMPENSATION	YES	YES	YES	YES
DIGITAL ANALYSIS	YES	YES	YES	YES
BRACKET AVAILABLE	YES	YES	YES	YES
POWER SUPPLY	13.8 Vdc	13.8 Vdc	13.8 Vdc	13.8 Vdc
CONSUMPTION	23 mA	23 mA	23 mA	23 mA
HOUSING	ABS	ABS	ABS	ABS
PET IMMUNITY	-	-	YES	YES
OPERATING TEMPERATURE	from -10 °C to +40 °C			
DIMENSIONS	110 x 60 x 46 mm			